

PENTABRIDNI SNIMAČI (DVR)

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
<p>NVR301-04Q</p>  <p>EASY UNV Better Security, Better World.</p> <p>4K ULTRAHD</p>	6452	<p>4-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF Podržava TVI,AHD, CVI,CVBS kamere do 8MP na kanalu 1 Rezolucija snimanja IP kamera: do 8mp (2 IP kamere ili svih 6) Video kompresija: H.265, H.264 Video/audio ulazi: 4ch BNC, 1ch audio Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio Ulazno/Izlazni saobraćaj: 40/60 Mbps Smart funkcije: Motion detection, Face detection, intrusion detection, cross line detection, audio detection, defocus i scene change Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm x240mmx 46mm (10.2" x 9.4"x1.8")</p>	92,40	77,00
<p>XVR301-04Q</p>  <p>EASY UNV Better Security, Better World.</p> <p>4K ULTRAHD</p>	6717	<p>4-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF Podržava TVI,AHD, CVI, CVBS kamere do 8MP/15fps na kanalu 1 Rezolucija snimanja IP kamera: do 8mp (2 IP kamere ili svih 6) Video kompresija: H.265, H.264 Video/audio ulazi: 4ch BNC, 1ch audio Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio Ulazno/Izlazni saobraćaj: 48/60 Mbps Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm x240mmx 46mm (10.2" x 9.4"x1.8")</p>	120,00	100,00
<p>NVR301-08Q</p>  <p>EASY UNV Better Security, Better World.</p> <p>4K ULTRAHD</p>	6453	<p>8-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF Podržava TVI,AHD, CVI,CVBS kamere do 8MP na kanalu 1 i 2 Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12) Video kompresija: H.265, H.264 Video/audio ulazi: 4ch BNC, 1ch audio Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio Ulazno/Izlazni saobraćaj: 40/64 Mbps Smart funkcije: Motion detection, Face detection, intrusion detection, cross line detection, audio detection, defocus i scene change Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm x240mmx 46mm (10.2" x 9.4"x1.8")</p>	145,20	121,00
<p>XVR301-08Q</p>  <p>EASY UNV Better Security, Better World.</p> <p>4K ULTRAHD</p>	6716	<p>8-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF Podržava TVI,AHD, CVI, CVBS kamere do 8MP/15fps na kanalu 1 i 2 Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12) Video kompresija: H.265, H.264 Video/audio ulazi: 4ch BNC, 1ch audio Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio Ulazno/Izlazni saobraćaj: 56/64 Mbps Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm x240mmx 46mm (10.2" x 9.4"x1.8")</p>	204,00	170,00

PENTABRIDNI SNIMAČI (DVR)

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
NVR302-08U	5850	<p>8-KANALNI PENTABRIDNI HD SNIMAČ HDTVI, IP, CVBS, CVI, AHD Rezolucija snimanja: 8MP@8fps, 5MP@12fps, 4MP@15fps, 3MP@18fps, 2MP@25fps, 720P@30fps Frame rate po kanalima: 2x4K@30, 2x6MP@30, 3x5MP@30, 4x4MP@30, 4x3MP@30, 6x3MP@25, 8x1080p@30, 16x720p@30 Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 16IP kamera), svaki kanal do 8mpx. Ulazno/Izlazni saobraćaj: 80/64 Mbps Video kompresija: H.265/H.264 video kompresija, Video/audio ulazi: 8ch BNC, 4ch audio RCA, 1xCVBS izlaz Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart funkcije: Alarm Notification/Alarm trigger(Face detection, Intrusion, cross line, Audio detection, Defocus,Scene Change) Alarmni Ulaz/Izlaz: 8/4 Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 2.0 interfejs, 1xUSB 3.0 interfejs, 1x RS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 2 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 380mm x315mmx 49mm, Težina 1.9Kg</p>	266,40	222,00
NVR302-16Q	5869	<p>16-KANALNI PENTABRIDNI HD SNIMAČ HDTVI, IP, CVBS, CVI, AHD Rezolucija snimanja: 8MP@8fps, 5MP@12fps, 4MP@15fps, 3MP@18fps, 2MP@25fps, 720P@30fps Frame rate po kanalima: 2x4K@30, 2x6MP@30, 3x5MP@30, 4x4MP@30, 4x3MP@30, 6x3MP@25, 8x1080p@30, 16x720p@30 Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP kamere), svaki kanal do 8mpx. Ulazno/Izlazni saobraćaj: 72/80 Mbps Video kompresija: H.265/H.264 video kompresija, Video/audio ulazi: 16ch BNC, 1ch RCA Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA Smart funkcije: * za IP kamere: Alarm Notification/Alarm trigger(Face detection, Intrusion, cross line, Audio detection, Defocus,Scene Change) * za Analogne kamere: 2-channel VCA analysis(Intrusion Detection,Cross Line Detection) Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 2.0 interfejs, 1xUSB 3.0 interfejs, 1x RS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 2 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 380mm x315mmx 49mm, Težina 1.9Kg</p>	264,00	220,00
XVR302-16Q	6713	<p>16-KANALNI PENTABRIDNI HD SNIMAČ HDTVI, IP, CVBS, CVI, AHD Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF Podržava 8MP@15fps na prva 4 kanala Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP kamere), svaki kanal do 8mpx. Ulazno/Izlazni saobraćaj: 72/80 Mbps Video kompresija: H.265/H.264 video kompresija, Video/audio ulazi: 16ch BNC, 1ch RCA Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 2 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 380mm x315mmx 53mm, Težina 1.9Kg</p>	288,00	240,00

MREŽNI VIDEO SNIMAČI

NVR

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
NVR301-04S2   	5864	4-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/izlazni saobraćaj: 40/40 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI/VGA (FULL HD), Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection ONVIF conformance: Profile S, Profile G, Profile T Pretraga snimka po smart funkcijama: Face search, Behavior search Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0., Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 48V DC, Potrošnja 10W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg	108,00	90,00
NVR301-04E   	5849	4-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/izlazni saobraćaj: 40/64 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object left behind, Object removed Pretraga snimka po smart funkcijama: Face search, Behavior search Statističke analize: Brojanje ljudi ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 3xUSB 2.0 interfejs, 4x Alarmni ulaz, 1x Alarmni izlaz Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm×240mm×44mm, Težina 1.12Kg	128,40	107,00
NVR301-08S2  	5859	8-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/izlazni saobraćaj: 50/40 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI/VGA (FULL HD), Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection ONVIF conformance: Profile S, Profile G, Profile T Pretraga snimka po smart funkcijama: Face search, Behavior search Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0., Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 52V DC, Potrošnja 9W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg	144,00	120,00
NVR301-08E   	5854	8-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/izlazni saobraćaj: 60/40 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object left behind, Object removed Pretraga snimka po smart funkcijama: Face search, Behavior search Statističke analize: Brojanje ljudi ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 3xUSB 2.0 interfejs, 4x Alarmni ulaz, 1x Alarmni izlaz Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm×240mm×44mm, Težina 1.12Kg	180,00	150,00

MREŽNI VIDEO SNIMAČI

NVR

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
<p>NVR302-16E-B</p>  <p>PRIME UNV Better Security, Better World.</p> <p>4K ULTRAHD</p>	5597	<p>16-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 160/320 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Face Recognition uz UIA1000 Smart Bar (Kamera mora da podržava Face Detection), Object left behind, Object removed Pretraga snimka po smart funkcijama: Face search, Behavior search Statističke analize: Brojanje ljudi ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 8x Alarmni ulaz, 2x Alarmni izlaz Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 2 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 20W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 380mm × 315mm ×46mm, Težina 2.48Kg</p>	330,00	275,00
<p>NVR301-16E</p>  <p>EASY UNV Better Security, Better World.</p> <p>4K ULTRAHD</p>	6454	<p>16-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 80/80 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking Pretraga snimka po smart funkcijama: Face search, Behavior search Statističke analize: Brojanje ljudi ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 3xUSB 2.0 interfejs, 4x Alarmni ulaz, 1x Alarmni izlaz Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm×240mm×44mm, Težina 1.12Kg</p>	204,00	170,00
<p>NVR302-16E-IF-BA</p>  <p>PRIME UNV Better Security, Better World.</p> <p>4K ULTRAHD</p>	6600	<p>16-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 160/320 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking Face recognition sa face capture kamerom: 4 Face recognition sa obicnom kamerom: 1 Do 16 biblioteka lica sa kapacitetom od 50000 slika lica Pretraga snimka po smart funkcijama: Face search, Behavior search Statističke analize: Brojanje ljudi ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 8x Alarmni ulaz, 2x Alarmni izlaz Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 2 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 20W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 380mm × 315mm ×46mm, Težina 2.48Kg</p>	426,00	355,00

MREŽNI VIDEO SNIMAČI

NVR

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
NVR304-32E-B	5852	<p>32-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 320/320 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Face Recognition uz UIA1000 Smart Bar (Kamera mora da podržava Face Detection), Object left behind, Object removed Pretraga snimka po smart funkcijama: Face search, Behavior search Statističke analize: Brojanje ljudi ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 16x Alarmni ulaz, 4x Alarmni izlaz, RS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 4 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 440mm × 344mm × 44mm, Težina 3.14Kg</p>	696,00	580,00
NVR304-32E-IF	6714	<p>32-KANALNI MREŽNI SNIMAČ Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Live view/Playback: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 320/320 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking Face recognition sa face capture kamerom: 4 Face recognition sa obicnom kamerom: 1 Do 16 biblioteka lica sa kapacitetom od 50000 slika lica Pretraga snimka po smart funkcijama: Face search, Behavior search Statističke analize: Brojanje ljudi ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 16x Alarmni ulaz, 4x Alarmni izlaz Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 4 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 440mm × 344mm × 50mm, Težina 3,14Kg</p>	762,00	635,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC2122LR3-PF40M-D	5599	<p>2 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: 1080P (1920*1080), Max 30fps Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS, Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm@F2.0 Osetljivost: Colour: 0.02Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 4.5W Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 167.3 × 62.9 × 62.7mm težina: 0,37kg</p> <p>Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN</p>	80,40	67,00
IPC2122LR3-PF40-E	6234	<p>2 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: 1080P (1920*1080), Max 25fps Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS, Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm@F2.0 Osetljivost: Colour: 0.02Lux (F2.0, AGC ON) 0 Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP Mrežni stadardi: ONVIF (Profile T), API Kompresija: Ultra 265, H.265, H.264 Smart funkcije: Motion detection Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Digital defog Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5.5W Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 167.3 × 62.9 × 62.7mm težina: 0,27kg</p> <p>Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-JB05-A-IN, TR-UP06-C-IN, TR-A01-IN</p>	66,00	55,00
IPC2322LBR3-SPZ28-D	5592	<p>2 MP IR Varifokalna bullet Mrežna Kamera Rezolucija snimanja: : 1080P (1920*1080), Max 30fps Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8 ~ 12mm, motorizovani zoom Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6.5W Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 240.3 × 86.4 × 75.6mm, težina: 1kg</p> <p>Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN</p>	150,00	125,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC2122SR3-UPF40-C	6327	<p>2 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: 1080P (1920*1080), Max 30fps Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS, Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm@F1.6 Osetljivost: Colour: 0.001Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, 120db WDR IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Crossing line Detection, Motion detection, Tampering alarm, Scene Change Detection, Defocus Detection, People Counting, Face Detection. Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6W Radna Temperatura: -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 157.3 × 62.4 × 63mm, 0,45kg Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN</p>	126,00	105,00
IPC2222EBR5-HDUPF40	6337	<p>2 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: 1080P (1920*1080), Max 60fps Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm@F1.6 Osetljivost: Colour: 0.001Lux (F1.6, AGC ON) 0Lux with IR on WDR: 120db IC domet: do 50m Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Scene Change Detection, Defocus Detection, People counting, Face detection. Ostale Karakteristike: Digital Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 7.5W Radna Temperatura: -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): 253.4 × 86 × 71.7mm (9.98" × 3.4" × 2.8") Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-JB06-A-IN, TR-UP06-C-IN</p>	180,00	150,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC2222ER5-DUPF40-C	6333	<p>2 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: 1080P (1920*1080), Max 30fps Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm@F1.2 Osetljivost: Colour: 0.0005Lux (F1.2, AGC ON) 0Lux with IR on WDR: 120db IC domet: do 50m Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Scene Change Detection, Defocus Detection, People counting, Face detection. Ostale Karakteristike: Digital Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 9W Radna Temperatura: -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): 253.4 × 86 × 71.7mm (9.98" × 3.4" × 2.8")</p> <p>Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-JB06-A-IN, TR-UP06-C-IN</p>	180,00	150,00
IPC322LR3-VSPF28-E	5588	<p>2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera Rezolucija snimanja: 1080P (1920*1080), Max 30fps Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm @F2.0 Osetljivost: 0.02Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Motion detection. Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 4W Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ109 x 81mm težina: 0,35kg</p> <p>Kompatibilni nosači i pribor: TR-A01-IN, TR-UM06-E-IN, TR-UP06-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN</p>	78,00	65,00
IPC3232LR3-VSPZ28-D	5851	<p>2 MP IR Varifokalna Dome Mrežna Kamera Rezolucija snimanja: : 1080P (1920*1080), Max 30fps Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8 ~ 12mm, motorizovani zoom Osetljivost:0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T, Profile G), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: Digital defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6.5W Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ148 x 111.3mm, težina: 0.92kg</p> <p>Kompatibilni nosači i pribor: TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-JB07/WM04-B-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN</p>	150,00	125,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC322SR3-VSF28W-D	6329	<p>2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera, WIFI Rezolucija snimanja: 1080P (1920*1080), Max 20fps Čip: 1/2.7", progressive scan, 2.0 megapixel, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm @F2.0 Osetljivost: 0.02Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25% Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ109 x 81mm težina: 0,35kg</p> <p>Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN</p>	120,00	100,00
IPC322ER3-DUVPF28-C	6325	<p>2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera Rezolucija snimanja: 1080P (1920*1080), Max 30fps Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm @F1.6 Osetljivost: Colour: 0.001Lux (F1.6, AGC ON) 0Lux with IR, IR-cut filter, WDR: 120db IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Audio Detection, Scene Change Detection, Defocus Detection, People counting, Face detection. Ostale Karakteristike: Digital Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 4W Radna Temperatura: -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ109 x 81mm težina: 0,35kg</p> <p>Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN</p>	126,00	105,00
IPC6412LR-X5P	5873	<p>2Mpx unutrašnja Mini PTZ kamera Rezolucija snimanja: : 2MP (1920*1080), Max 30fps Čip: 1/2.9" progressive scan, 2.0 megapixel, CMOS Šater: Auto/Manual, 1 s ~ 1/100000 s Optika: 2.7~13.5mm, Automatski fokus i motorizovani zoom Osetljivost: Colour: 0.03 lux (F1.2,AGC ON) 0 lux with IR IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 12W Radna Temperatura: -10°C ~ 50°C (-14°F ~ 122°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 129 x 143 mm, težina: 0,75kg</p> <p>Kompatibilni nosači i pribor: TR-WM03-B-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN, TR-JB07/WM03-F-IN</p>	168,00	140,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC2124LR3-PF40M-D	5590	<p>4 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: : 4MP (2592*1520), Max 20fps Čip: 1/3", 4.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm@F2.0 Osetljivost: Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 4W Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 167.3 × 62.9 × 62.7mm težina: 0,37kg</p> <p>Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN</p>	94,80	79,00
IPC2124LR3-PF28M-D	6619	<p>4 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: : 4MP (2592*1520), Max 20fps Čip: 1/3", 4.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm@F2.0 Osetljivost: Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 4W Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 167.3 × 62.9 × 62.7mm težina: 0,37kg</p> <p>Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN</p>	94,80	79,00
IPC2224SR5-DPF40-B	5593	<p>4 MP IR Fiksna Bullet Mrežna Kamera sa WDR-om Rezolucija snimanja: 4MP (2592*1520), Max 20fps; 4MP (2560*1440), Max 25fps; 3MP (2048*1520), Max 30fps; Čip: 1/3", 4.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm @F2.0 Osetljivost: 0.03Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db IC domet: do 50m Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection. Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat., Statističke analize: Brojanje Ljudi Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 9W Radna Temperatura: -35°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 253.4 × 86 × 71.7mm, težina: 1kg</p> <p>Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN</p>	160,80	134,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)		
IPC2224SA-DF40K	6715	<p>4 MP Lighthunter Deep learning Bullet Mrežna Kamera sa WDR-om Rezolucija snimanja: 4MP (2592*1520), Max 30fps Čip: 1/1,8", 4.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm @F1.6 Osetljivost: 0.001Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db IC domet: do 50m Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Motion detection, tampering, audio loss detection, cross line, intrusion, object removed, object left behind, defocus, scene change, human body detection Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 9W Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 245.6x85.7x85.4mm, težina: 0.90kg Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, R-JB06-A-IN</p>	174,00	145,00		
		IPC324LBR3-SPZ28-D	5865	<p>4 MP IR Varifokalna Bullet Mrežna Kamera Rezolucija snimanja: : 4MP (2592*1520), Max 20fps; Čip: 1/3", 4.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8 ~ 12mm, motorizovani zoom Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6.5W Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 240.3 × 86.4 × 75.6mm, težina: 1kg</p>	174,00	145,00
		IPC324LR3-VSPF28-D	5596	<p>4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera Rezolucija snimanja: : 4MP (2592*1520), Max 20fps Čip: 1/3", progressive scan, 4.0 megapixel, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm @F2.0 Osetljivost: 0.03Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 4W Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ109 x 81mm težina: 0,35kg</p>	106,80	89,00
		<p>Kompatibilni nosači i pribor: TR-A01-IN, TR-UM06-E-IN, TR-UP06-IN, TR-JB03-G-IN, TR-JB07-WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN</p>				

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC3614LR3-PF28-D	6449	<p>4 MP IR Fiksna Dome Mrežna Kamera Rezolucija snimanja: 4MP (2592*1520), Max 20fps Čip: 1/3", progressive scan, 4.0 megapixel, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm @F2.0 Osetljivost: 0.03Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Smart funkcije: Motion detection, alarm tampering, intrusion detection i human body detection Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 4W Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ118 x 96mm (Φ4.6" x 3.8"), težina 350g</p>	138,00	115,00
IPC3234LR3-VSPZ28-D	5595	<p>4 MP IR Varifokalna Dome Mrežna Kamera Rezolucija snimanja: : 4MP (2592*1520), Max 20fps; Čip: 1/3", 4.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8 ~ 12mm, motorizovani zoom Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm. Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6W Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ148 x 111.3mm, težina: 0.92kg</p>	174,00	145,00
IPC744SR5-PF40-32G	6336	<p>4 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: 2592x1520 resolution, 20fps Čip: 1/3", 4.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm@F2.0 Osetljivost: Color: 0.02Lux (F2.0, AGC ON) 0Lux with IR on, 120db WDR IC domet: do 50m PTZ komande: 16 patrola i 32 preseta po patroli, Home pozicija. Interfejsi: 10/100M Base-TX Ethernet, ugrađen 32GB eMMC, 2x Alarmnih ulaza, 1x Alarmnih izlaza Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Audio Detection, Defocus Detection, People counting, Face detection. Ostale Karakteristike: Digital Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod Zaštita: IP66 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 17.23W Radna Temperatura: -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): 357x 106 x 194mm (14.1" x 4.2" x 7.7")</p>	270,00	225,00

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC325ER3-DUVPF28	5857	<p>5 MP IR Fiksna Dome Mrežna Kamera sa WDR-om Rezolucija snimanja: 5MP (2592*1944), Max 20fps; 5MP (2592*1944), Max 25fps (WDR OFF) Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm @F1.6 Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB, 2x Audio ulaz, 1x Audio izlaz, 1x Alarm ulaz, 1x Alarmni izlaz Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection. Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat., Statističke analize: Brojanje Ljudi Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5W Radna Temperatura: -35°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ108.5 x 81mm, težina: 0.45kg</p> <p>Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN</p>	162,00	135,00
IPC2125SR3-ADUPF40	6712	<p>5 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: 5MP (2592*1944) Max 20fps, 5MP (2592*1944), Max 25fps (WDR OFF); Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS, Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4.0mm@F1.6 Osetljivost: Colour: 0.005Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, 120db WDR IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Motion detection, tampering, audio loss detection, cross line, intrusion, object removed, object left behind, defocus, scene change, face, people counting Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6W Radna Temperatura: -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 157.3 × 62.4 × 63mm, 0,45kg Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN</p>	156,00	130,00



NAZIV ARTIKLA

Kat.br.

Karakteristike

CENA EUR
(gotovinski)CENA EUR
(račun bez PDV)

IPC2325EBR5-DUPZ



PRIME

5 MP IR Varifokalna Bullet Mrežna Kamera sa WDR-om

Rezolucija snimanja: 5MP (2592*1944), Max 20fps; 5MP (2592*1944), Max 25fps (WDR OFF)

Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.7 ~ 13.5mm, AF automatski fokus motorizovanim zoom-om

Osetljivost: 0.002Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, **WDR: 120db**

IC domet: do 50m

Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB, 2x Audio ulaz, 1x Audio izlaz, 1x Alarm ulaz, 1x Alarmni izlaz

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni stadardi: ONVIF (Profile S, Profile T, Profile G), API

5591 **Kompresija:** Ultra 265, H.265, H.264, MJPEG

288,00

240,00

Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.

Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat., **Statističke analize:** Brojanje Ljudi

Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod

Zaštita: IP67

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 10W

Radna Temperatura: -35°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 253.4 × 86 × 71.7mm, težina: 1kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC3635ER3-DUPZ	5860	<p>5 MP IR Varifokalna Dome Mrežna Kamera sa WDR-om</p> <p>Rezolucija snimanja: 5MP (2592*1944), Max 20fps; 5MP (2592*1944), Max 25fps (WDR OFF) Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.7 ~ 13.5mm, AF automatski fokus motorizovanim zoom-om Osetljivost: 0.002Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB, ugrađen mikrofoni Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF (Profile S, Profile T, Profile G), API Kompresija: Ultra 265, H.265, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection. Inteligentne identifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat., Statističke analize: Brojanje Ljudi Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 8,16W Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ129 x 110mm, težina: 0.82kg</p> <p>Kompatibilni nosači i pribor: TR-WM03-B-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN, TR-JB07/WM03-F-IN.</p>	288,00	240,00



IPC815SR-DVPPF14

	6451	<p>Fisheye IP kamera</p> <p>Čip: Image sensor 1/2.8", progressive scan, 5.0 megapixel, CMOS Panoramic image: 360 stepeni Optika: 1.4mm@F2.0 Rezolucija snimanja: 2592x1944 resolution, 30fps Osetljivost: Colour: 0.01 Lux (F2.0, AGC ON) 0 Lux with IR, WDR 120db Interfejsi: 1x RJ45, Slot za SD karticu do 256GB, Protokoli: Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni standardi: ONVIF Smart funkcije: Motion detection, Tampering alarm, Heat map Integrisan mikrofoni. Kompresija: H.265, H.264, MJPEG IC osvetljenje: Domet IC dioda do 10m, Zaštita: IP67, IK10 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5W Radna Temperatura: -40°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije: Φ125 x 43.7 mm (Φ4.9" x 1.7") Kompatibilni nosači i pribor: TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN</p>	294,00	245,00
--	------	--	--------	--------



NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
IPC2128SR3-DPF40 4K Bullet kamera	5863	<p>4K IR Fiksna Bullet Mrežna Kamera sa WDR-om Rezolucija snimanja: 8MP (3840*2160), Max 20fps Čip: 1/2.5", 8.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 4mm @F2.0 Osetljivost: 0.05Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection. Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat, Statističke analize: Brojanje Ljudi Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 8W Radna Temperatura: -30°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 191.3×72.6×70.9mm, težina: 0.5kg</p> <p>Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN</p>	186,00	155,00



PRIME

Better Security, Better World.

IPC3618SR3-DPF28M
4K Turret kamera


PRIME

Better Security, Better World.

5862	<p>4K IR Fiksna Turret Mrežna Kamera sa WDR-om Rezolucija snimanja: 8MP (3840*2160), Max 20fps Čip: 1/2.5", 8.0 megapixel, progressive scan, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm @F2.0 Osetljivost: 0.05Lux (F 2.0, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection. Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat, Statističke analize: Brojanje Ljudi Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5.5W Radna Temperatura: -30°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (ΦxV): Φ126 x 94mm, težina: 0.45kg</p> <p>Kompatibilni nosači i pribor: TR-WM03-B-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN, TR-JB07/WM03-F-IN</p>	186,00	155,00
------	--	--------	--------

NAZIV ARTIKLA

Kat.br.

Karakteristike

CENA EUR
(gotovinski)CENA EUR
(račun bez PDV)**IPC3238ER3-DVZ**
4K Dome kamera

5874

4K IR Varifokalna Dome Mrežna Kamera sa WDR-om

Rezolucija snimanja: 8MP (3840*2160), Max 30fps; 2MP (1920*1080), Max 30fps

Čip: 1/2.5", 8.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8 ~ 12mm@F1.6

Osetljivost: 0.02Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, **WDR: 120db**

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 1x Alarmni ulaz, 1x Alarmni izlaz, BNC izlaz, DC12V izlaz sa PoE napajanjem.

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni stadardi: ONVIF (Profile S, Profile T), API

Kompresija: **Ultra 265**, H.265, H.264, MJPEGSmart funkcije: **Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.**Inteligentne indentifikacije: **Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat., Statističke analize: Brojanje Ljudi**Ostale Karakteristike: **2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod**Zaštita: **IP67, IK10**

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 8.7W

Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ148 x 111.3mm, težina: 0.92kg

Kompatibilni nosači i pribor: TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-JB/WM04-B-IN

780,00

650,00

IPC268ER9-DZ
4K Bullet kamera

5881

4K IR Varifokalna Bullet Mrežna Kamera sa WDR-om

Rezolucija snimanja: 8MP (3840*2160), Max 30fps; 2MP (1920*1080), Max 30fps

Čip: 1/2.5", 8.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8 ~ 12mm@F1.6, P-Iris, AF Automatski fokus sa motorizovanim zoom-om

Osetljivost: 0.02Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, **WDR: 120db**

IC domet: do 100m

Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 2x Alarmni ulaz, 1x Alarmni izlaz, BNC izlaz, 1x RS485, Audio kabl

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni stadardi: ONVIF (Profile S, Profile T, Profile G), API

Kompresija: **Ultra 265**, H.265, H.264, MJPEGSmart funkcije: **Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.**Inteligentne indentifikacije: **Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat., Statističke analize: Brojanje Ljudi**Ostale Karakteristike: **2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod**Zaštita: **IP67**

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3at), max 13.7W

Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 305.5 × 104.1 × 97.3mm, težina: 1.65kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN

804,00

670,00

NAZIV ARTIKLA

Kat.br.

Karakteristike

CENA EUR
(gotovinski)CENA EUR
(račun bez PDV)

IPC6412LR-X5P



EASY

UNV®
Better Security, Better World.

5873

2Mpx unutrašnja Mini PTZ kamera

Rezolucija snimanja: : 2MP (1920*1080), Max 30fps

Čip: 1/2.9", 2.0 megapixel, progressive scan, CMOS, Blenda: F1.5 ~ F4.0

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.7~13.5mm, AF automatski fokus sa motorizovanim zoom-om

Osetljivost: 0.03Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter,

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, Ugrađen mikrofoni

PTZ komande: 1024 preseta, Home pozicija.

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,

UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF (Profile G, Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection

Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS, DWDR

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE802.3 af), 12W

Radna Temperatura: -10°C ~ 50°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ129mm×143mm, težina: 0.75kg

Kompatibilni nosači i pribor: TR-WM03-B-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN, TR-JB07/WM03-F-IN

168,00

140,00

IPC6415SR-X5UPW



EASY

UNV®
Better Security, Better World.

6450

5 MP Unutrašnja mini PTZ IP kamera

Rezolucija snimanja: 5M (2592*1944):Max. 30 fps

Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.7~13.5mm, AF automatski fokus sa motorizovanim zoom-om

Osetljivost: 0.002Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter,

IR domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, Ugrađen mikrofoni i zvučnik

PTZ komande: 1024 preseta, Home pozicija.

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,

UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF (Profile G, Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, line crossing, intrusion detection, ulaz i izlaz iz oblasti, object left behind i object removed, face detection, people counting, defocus i promena scene

Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS, DWDR

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE802.3 af), 12W

Radna Temperatura: -10°C ~ 50°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ129mm×143mm, težina: 0.75kg

Može da radi samostalno sa EZview!

282,00

235,00

NAZIV ARTIKLA

Kat.br.

Karakteristike

CENA EUR
(gotovinski)CENA EUR
(račun bez PDV)

IPC672LR-AX4DUPKC



NOVO

LIGHTHUNTER



EASY

UNV®
Better Security, Better World.

2 MP Outdoor mini PTZ kamera sa integrisanom sirenom
Rezolucija snimanja: 1080P (1920*1080), Max 30fps
Čip: 1/2.8", progressive scan , 2.0 megapixel, CMOS
Shutter: Auto/Manual, 1 ~ 1/100000s
Optika: 2.8-12mm AF automatsko fokusiranje i motorizovan 4x opticki zoom
Osetljivost: 0.001Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 50m
Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 128GB
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP , PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP , 802.1x , SNMP, SSL
Mrežni stadardi: ONVIF(Profile S, Profile G, Profile T), API
PTZ funkcije: Preset patrol, Route patrol (256 preseta)
Kompresija: Ultra 265, H.265, H.264, MJPEG
Smart funkcije: Motion detection, Tampering alarm, Audio Detection, Human body detection i Auto tracking
Kamera poseduje integrisanu sirenu od 52db, kao i mikrofoni i zvučnik sa mogućnošću da se izabere jedna od 10 poruka na engleskom da upozori uljeza ukoliko upadne u nedozvoljeno područje
 (moguće ubaciti jednu poruku na srpskom ili nekom drugom jeziku)
Zaštita: IP66
Napajanje i potrošnja: DC 12V±25%, PoE (IEEE802.3 at)
Radna Temperatura: -20°C ~ 60°C (-4°F to 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije: Φ133mm*269.4mm (Φ5.2"x 10.6")

6616

288,00

240,00

IPC6322SR-X22P-D



NOVO

LIGHTHUNTER



EASY

UNV®
Better Security, Better World.

2 MP Speed Dome PTZ kamera sa 22x optičkim zoom-om
Rezolucija snimanja: 2MP (1920*1080), Max 30fps
Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS, Blenda: F1.5 ~ F3.8
Šater: Auto/Manual, 1 ~ 1/100000s
Optika: 5.2 ~ 114.4mm, AF automatski fokus sa motorizovanim zoom-om
Osetljivost: 0.003Lux (F1.5, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db
IR domet: do 150 m
Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 1x Alarmni ulaz, 1x Alarmni izlaz
PTZ komande: Preset Patrol, 1024 preseta, Home pozicija.
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
Mrežni stadardi: ONVIF (Profile G, Profile S, Profile T), API
Kompresija: Ultra 265, H.265, H.264, MJPEG
Smart funkcije: **Cross line, intrusion, object removed, object left behind, master-slave linkage, face detection, people counting, auto tracking**
Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS
Zaštita: IP66
Napajanje: DC 12V±10%, PoE (PSE potreban)
Radna Temperatura: -40°C ~ 65°C (-40°F ~ 149°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije: (ΦxV):Φ220 × 369mm, težina: 3,4kg

6761

720,00

600,00

NAZIV ARTIKLA

Kat.br.

Karakteristike

CENA EUR
(gotovinski)CENA EUR
(račun bez PDV)

IPC6222ER-X30-B



5876

2 MP Speed Dome PTZ kamera sa 30x optičkim zoom-om**Rezolucija snimanja:** 2MP (1920*1080), Max 30fps**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS**Šater:** Auto/Manual, 1 ~ 1/100000s**Optika:** 4.5 ~ 135mm, AF automatski fokus sa motorizovanim zoom-om od 30x**Osetljivost:** 0.001Lux (F1.5, AGC ON) 0Lux with IR on, IR-cut filter, **WDR: 120db****IC domet:** do 150m**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz,

1x Alarmni ulaz, 1x Alarmni izlaz, Audio kabl

PTZ komande: 16 patrola i 32 preseta po patroli, Home pozicija.**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,

UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni stadardi: ONVIF (Profile G, Profile S, Profile T), API**Kompresija:** Ultra 265, H.265, H.264, MJPEG**Smart funkcije:** Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection,

Audio Detection, Digitalni zoom 16x, Auto tracking

Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat., Statističke

analize: Brojanje Ljudi

Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS**Zaštita:** IP66**Napajanje i potrošnja:** AC 24V±25%, DC 24V±25%, PoE (PSE Required), 9 ~ 42W**Radna Temperatura:** -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)**Dimenzije (ΦxV):** Ø 227 x 359.4mm, težina: 5.28kg**Kompatibilni nosači i pribor:** TR-CE45-IN, TR-UF45-A-IN, TR-SE45-IN, TR-SE45-A-IN, TR-WE45-IN,

TR-WE45-A-IN, TR-WE45-B-IN, TR-JB12-IN, TR-UP-A-IN, TR-UC08-A-IN, TR-UP08-B-IN, TR-UC08-B-

IN

864,00

720,00

IPC6854SR-X38UP-VC



6338

4 MP Speed Dome AI Metadata PTZ kamera sa 38x optičkim zoom-om**Rezolucija snimanja:** 2688*1520 resolution, 60fps**Čip:** 1/1.8", 4.0 megapixel, progressive scan, CMOS**Šater:** Auto/Manual, 1 ~ 1/100000s**Optika:** 5.7 ~ 216.6mm, automatski fokus**Osetljivost:** Color: 0.0005Lux (F1.3, AGC ON) 0Lux with IR on, **120db WDR****IC domet:** do 250m**PTZ komande:** 16 patrola i 1024 preseta po patroli, Home pozicija.**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD do 256GB, 2x Alarmna ulaza, 1 Alarmni izlaz, RS485**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,

UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni stadardi: ONVIF (Profile S, Profile T), API**Kompresija:** Ultra 265, H.265, H.264, MJPEG**Smart funkcije:** Intrusion Detection, Cross line, Object left behind and object removed detection, Motion

detection, Tampering alarm, Audio Detection, Defocus Detection, People counting, Face detection.

Ostale Karakteristike: Optički Defog i Digitalni Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI,

Corridor mod, EIS (žiroskopska stabilizacija slike), Umanjuje False Alarme, Metadata (Boja automobila,

da li je motocikl ili auto, kod ljudi godine, naočare da li nosi, pol osobe...)

Zaštita: IP66**Napajanje i potrošnja:** AC 24V ±25%, DC 24V ±25%, PoE++ (IEEE 802.3bt) (IEEE802.3bt switch

required), potrošnja od 16-51W

Radna Temperatura: -40°C ~ 70°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)**Dimenzije (ΦxV):** 357× 106 × 194mm (14.1" × 4.2" × 7.7")**Kompatibilni nosači i pribor:** TR-CE45-IN, TR-UF45-A-IN, TR-SE45-IN, TR-SE45-A-IN, TR-WE45-A-

IN, TR-WE45-B-IN, TR-JB12-IN, TR-UP08-A-IN, TR-UC08-A-IN, TR-UP08-B-IN, TR-UC08-B-IN

2.400,00

2.000,00

NAZIV ARTIKLA

Kat.br.

Karakteristike

CENA EUR
(gotovinski)CENA EUR
(račun bez PDV)

SERVER UNICORN



6335

Glavne Karakteristike

- * **Stability:** Linux OS, dual-BIOS, redundant power, two-server hot standby
- * **Compatibility:** Third-party IP Cameras supported with standard ONVIF
- * **Access:** Browser/Server, Client/Server and mobile clients (both iOS and Android)
- * **Connection:** 1000 device connections, up to 2000 channels of high-definition network videos
- * **Management:** Unified management of NVR, IPC, decoder, network keyboard, cloud devices, alarm control panel and door access control, support devices' configuration import/export
- * **Storage:** Max 16 hard disks and 2 disk enclosures; expandable up to 48 disks with 672TB storage, recording backup, IPSAN storage
- * **Decoding:** Max 16×1080P decoding outputs in three screens, expandable up to 112×1080P in 15 screens with 2 decoding cards inserted
- * **Service:** Live view, playback, sequence, video wall, E-map, two-way audio, and alarm plan
- * **Reliability:** Support of HTTPS, 802.1x authentication, ARP protection, Telnet enabling/disabling, network fault tolerance, multi-IP configuration, load balancing, secure password and IP address filtering

6.189,60

5.158,00

Height: 3U, support mounting in standard 19" cabinet

477.1 mm × 481.6 mm × 130.5 mm (18.8"×19"×5.1") (including front panel)



HARD DISKOVI

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
WD10PURX-64KC9Y0   Better Security. Better World.	5885	<u>Izgrađen posebno za sigurnosne sisteme.</u> Kapacitet diska: 1TB Format: 3.5" Interfejs: SATA III Broj obrtaja u minuti: 5400 RPM Protok: 6 Gbps (600 MB/s) Keš memorija: 64MB	78,00	65,00
WD20PURX-64PFUY0   Better Security. Better World.	5886	<u>Izgrađen posebno za sigurnosne sisteme.</u> Kapacitet diska: 2TB Format: 3.5" Interfejs: SATA III Broj obrtaja u minuti: 5400 RPM Protok: 6 Gbps (600 MB/s) Keš memorija: 64MB	104,40	87,00
WD30PURX-64PFUY0   Better Security. Better World.	6328	<u>Izgrađen posebno za sigurnosne sisteme.</u> Kapacitet diska: 3TB Format: 3.5" Interfejs: SATA III Broj obrtaja u minuti: 5400 RPM Protok: 6 Gbps (600 MB/s) Keš memorija: 64MB	132,00	110,00
WD40PURX-64N96Y0   Better Security. Better World.	6130	<u>Izgrađen posebno za sigurnosne sisteme.</u> Kapacitet diska: 4TB Format: 3.5" Interfejs: SATA III Broj obrtaja u minuti: 7200 RPM Protok: 6 Gbps (600 MB/s) Keš memorija: 64MB	150,00	125,00

HARD DISKOVI

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
<p>WD60PURX-64WY0Y1</p>  	6332	<p><u>Izgrađen posebno za sigurnosne sisteme.</u></p> <p>Kapacitet diska: 6TB Format: 3.5" Interfejs: Sata III Broj obrtaja u minuti: 5400 RPM Protok: 6 Gbps (600 MB/s) Keš memorija: 64MB</p>	248,40	207,00
<p>WD82PURX-64GVLY0</p>  	6455	<p><u>Izgrađen posebno za sigurnosne sisteme.</u></p> <p>Kapacitet diska: 8TB Format: 3.5" Interfejs: Sata III Broj obrtaja u minuti: 5400 RPM Protok: 6 Gbps (600 MB/s) Keš memorija: 64MB</p>	345,60	288,00

SWITCH UREĐAJI

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
NSW2010-6T-POE-IN   Better Security, Better World.	6232	6×100Mbps network ports (RJ45), od toga 4 PoE porta Podržava: IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode):Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona PoE Budžet: 65W Maksimalna snaga porta: 30W Dimenzije: 160mm x 93mm x 32mm	54,00	45,00
NSW2010-10T-POE-IN   Better Security, Better World.	6235	10×100Mbps network ports (RJ45), od toga 8 PoE porta Podržava: IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode):Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 120W Maksimalna snaga porta: 30W Dimenzije: 220mm x 150mm x 44mm Moguća rek montaža 19" , dolazi uz switch	126,00	105,00
NSW2010-16T2GC-POE-IN   Better Security, Better World.	6334	16×100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta Podržava: IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode):Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 370W Maksimalna snaga porta: 250W Dimenzije: 440mm x 207mm x 45mm Moguća rek montaža 19" , dolazi uz switch	336,00	280,00
NSW2010-24T2GC-POE-IN    Better Security, Better World.	6326	24×100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 24 PoE porta Podržava: IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode):Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 24 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 370W Maksimalna snaga porta: 30W Dimenzije: 440mm x 207mm x 45mm Moguća rek montaža 19" , dolazi uz switch	396,00	330,00

NOSAČI I PRIBOR

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
UIA2000 Smart bar 	6599	Smart Bar za Uniview Prime snimače Podržava Ultra 265/H.265/H.264 video formate Do 16 bazi podataka lica sa kapacitetom od 50000 slika lica Funkcije: face recognition, monitoring management Face recognition sa face capture kamerom: 4 Face recognition sa običnom kamerom: 1 Napajanje: USB power supply Radna temperatura: -10°C ~ + 55°C (+14°F ~ +131°F) Dimenzije: 84mm × 32mm × 16mm (3.3"×1.3"×0.6")	480,00	400,00
TR-A01-IN NPT 3/4" Uvodnik Za Mrežne Kablove 	6233	Vodootporni uvodnik za mrežne kablove.	3,60	3,00
TR-JB05-A-IN 	5871	Nosač za mini bullet kamere Dimenzije: Φ93 × 93 × 39mm Težina: 0.2kg Materijal: Aluminijum	14,40	12,00
TR-JB07-D-IN 	5858	Nosač za kamere serije IPC23XX/222X, IPC74X i IPC252/26X Dimenzije: Φ125mm*125mm*55mm Težina: 0.75kg Materijal: Aluminijum	26,40	22,00
TR-JB03-G-IN 	5879	Nosač za Dome kamere serije IPC32x i IPC31x Dimenzije: φ106.6mm*36mm Težina: 0.2kg Materijal: Aluminijum	12,00	10,00
TR-JB04-C-IN 	5880	Nosač za Dome kamere serije IPC323X Dimenzije: Φ144.8mm*40mm Težina: 0.3kg Materijal: Aluminijum	14,40	12,00
TR-JB03-H-IN 	5878	Nosač za Dome kamere serije IPC363X Series, IPC36XXS/E i 4MP fisheye Dimenzije: Φ126mm*36mm Težina: 0.24kg Materijal: Aluminijum	12,00	10,00

NOSAČI I PRIBOR

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
TR-JB05-B-IN 	5861	Nosač za Dome kamere serije IPC21XX Dimenzije: $\Phi 104.4\text{mm} \times 54.5\text{mm}$ Težina: 0.36kg Materijal: Aluminijum	16,80	14,00
TR-JB07/WM03-G-IN 	5855	Zidni Nosač za Dome kamere serije IPC36XXL Dimenzije: $\Phi 125\text{mm} \times 125\text{mm} \times 228\text{mm}$ Težina: 1kg Materijal: Aluminijum	30,00	25,00
TR-JB07/WM04-B-IN 	5867	Zidni Nosač za Dome kamere serije IPC323x seriju dome kamera Dimenzije: $\Phi 125\text{mm} \times 125\text{mm} \times 252.5\text{mm}$ Težina: 0.98kg Materijal: Aluminijum	33,60	28,00
TR-JB07/WM03-F-IN 	5870	Zidni Nosač za Dome kamere serije IPC363X i IPC36XXS/E Dimenzije: $\Phi 125\text{mm} \times 125\text{mm} \times 233\text{mm}$ Težina: 0.98kg Materijal: Aluminijum	33,60	28,00
TR-WE45-IN 	5868	Zidni Nosač za PTZ kamere Dimenzije: $230.3\text{mm} \times 141\text{mm} \times 201.5\text{mm}$ Težina: 0.79kg Materijal: Aluminijum	24,00	20,00
TR-WE45-A-IN 	6330	Nosač PTZ kamere za unutrašnju i spoljašnju montažu Dimenzije: $216\text{mm} \times 141\text{mm} \times 314\text{mm}$ Težina: 1.0kg Materijal: Aluminijum	36,00	30,00
TR-CE45-IN 	5866	Plafonski nosač za PTZ kamere Dimenzije: $\Phi 116.5\text{mm} \times 239\text{mm}$ Težina: 0.67kg Materijal: Aluminijum	26,40	22,00

MREŽNI KABLOVI

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
UTP 24AWG CU LSZH CAT5E 	5978	Provodnički materijal: čvrsti goli bakar Izolacioni materijal: HDPE Omot: LSZH Boja: Siva Dužina: 305 m Na motalici.	0,42	0,35
UTP 24AWG CU/CCA CAT5E 	5979	Provodnički materijal: aluminijum obložen bakrom Izolacioni materijal: HDPE Omot: PVC Boja: Siva Dužina: 305 m Na motalici.	0,23	0,19
FTP 24AWG CU/CCA CAT5E 	5980	Provodnički materijal: aluminijum obložen bakrom Izolacioni materijal: HDPE Odvodna žica: aluminijum obložen bakrom Omot: PVC Boja: Siva Dužina: 305 m Na motalici.	0,29	0,24
FTP 24AWG CU LSZH CAT5E 	5981	Provodnički materijal: čvrsti goli bakar Izolacioni materijal: HDPE Omot: LSZH Boja: Siva Dužina: 305 m Na motalici.	0,64	0,53
UTP 23AWG CU LSZH CAT6 	5982	Provodnički materijal: čvrsti goli bakar Izolacioni materijal: HDPE Omot: LSZH Boja: Plava Dužina: 305 m Na motalici.	0,64	0,53
UTP 23AWG CU/CCA CAT6 	5983	Provodnički materijal: aluminijum obložen bakrom Izolacioni materijal: HDPE Omot: PVC Boja: Plava Dužina: 305 m Na motalici.	0,26	0,22

MREŽNI KABLOVI

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
U/FTP 23AWG CU LSZH CAT6 	5984	Provodnički materijal: čvrsti goli bakar Omot: LSZH Boja: Plava Dužina: 500 m Na metalici.	0,89	0,74
S/FTP CU LSZH CAT6A 	5985	Provodnički materijal: čvrsti goli bakar Širm: bakar Omot: LSZH Boja: Narandžasta Dužina: 500 m Drveni kotur.	0,96	0,80
FTP CU/CCA sa sajlom CAT6 	5987	Provodnički materijal: čvrsti goli bakar Izolacioni materijal: HDPE Omot: PE Sajla: čelična žica Boja: Crna Dužina: 305 m Drveni kotur.	0,90	0,75
S/FTP CU LSZH CAT7 	5986	Provodnički materijal: čvrsti goli bakar Širm: bakar Omot: LSZH Boja: Narandžasta Dužina: 500 m Drveni kotur.	0,88	0,73

MREŽNI PATCH KABLOVI

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
UTP CAT5E 0,25M	 6312	Patch kabl UTP CAT5E, 26AWG. Dužina kabla 0,25m sive boje.	0,52	0,43
UTP CAT5E 0,5M	 5735	Patch kabl UTP CAT5E, 26AWG. Dužina kabla 0,5m sive boje.	0,55	0,46
UTP CAT5E 1M	 5736	Patch kabl UTP CAT5E, 26AWG. Dužina kabla 1m sive boje.	0,65	0,54
UTP CAT5E 2M	 5737	Patch kabl UTP CAT5E, 26AWG. Dužina kabla 2m sive boje.	0,80	0,67
UTP CAT5E 3M	 5738	Patch kabl UTP CAT5E, 26AWG. Dužina kabla 3m sive boje.	1,00	0,83
UTP CAT5E 5M	 5739	Patch kabl UTP CAT5E, 26AWG. Dužina kabla 5m sive boje.	1,54	1,28
UTP CAT6 0,5M	 5740	Patch kabl UTP CAT6, 26AWG. Dužina kabla 0,5m sive boje.	0,83	0,69
UTP CAT6 1M	 5741	Patch kabl UTP CAT6, 26AWG. Dužina kabla 1m sive boje.	0,89	0,74
UTP CAT6 2M	 5742	Patch kabl UTP CAT6, 26AWG. Dužina kabla 2m sive boje.	1,15	0,96
UTP CAT6 3M	 5743	Patch kabl UTP CAT6, 26AWG. Dužina kabla 3m sive boje.	1,51	1,26
UTP CAT6 5M	 5744	Patch kabl UTP CAT6, 26AWG. Dužina kabla 5m sive boje.	1,94	1,62
FTP CAT6 0,5M	 5745	Patch kabl FTP CAT6, 26AWG. Dužina kabla 0,5m sive boje.	1,08	0,90
FTP CAT6 1M	 5746	Patch kabl FTP CAT6, 26AWG. Dužina kabla 1m sive boje.	1,24	1,03
FTP CAT6 2M	 5747	Patch kabl FTP CAT6, 26AWG. Dužina kabla 2m sive boje.	1,50	1,25
FTP CAT6 3M	 5748	Patch kabl FTP CAT6, 26AWG. Dužina kabla 3m sive boje.	1,80	1,50
FTP CAT6 5M	 5749	Patch kabl FTP CAT6, 26AWG. Dužina kabla 5m sive boje.	2,48	2,07

MODULI

NAZIV ARTIKLA	Kat.br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
 Modul RJ-45 UTP kat. 5E	4992	Modul RJ-45 UTP kat. 5E - LSA tip	0,72	0,60
 Modul RJ-45 UTP kat. 5E	4993	Modul RJ-45 UTP kat. 5E Spaja se bez alata	0,84	0,70
 Modul RJ-45 UTP kat. 6	4994	Modul RJ-45 UTP kat.6 Spaja se bez alata	1,08	0,90
 Modul RJ-45 STP kat. 6A	4995	Modul RJ-45 STP kat. 6A Spaja se bez alata	2,70	2,25
 Modul RJ-45 UTP kat. 5E	4714	Modul RJ-45 UTP kat. 5E - LSA tip	1,73	1,44
 Modul RJ-45 UTP kat. 5E	4711	Modul RJ-45 UTP kat. 5E - LSA tip	1,74	1,45
 Modul RJ-45 UTP kat. 6	4713	Modul RJ-45 UTP kat. 6 Spaja se bez alata.	2,52	2,10
 Modul RJ-45 STP kat. 6A	3340	Modul KJ cat.6a RJ45 STP TL Spaja se bez alata.	4,08	3,40
 Rotacioni CAT6 modul	6266	Rotacioni CAT6 modul.	1,20	1,00

NAZIV ARTIKLA

Kat.br.

Karakteristike

CENA EUR
(gotovinski)CENA EUR
(račun bez PDV)

URDB1 WiFi zvonca



- Ostvarivanje poziva na telefonu preko aplikacije Ezlive, pogledajte ko Vas zove bilo gde i bilo kad
Dve opcije za snimanje i skladištenje HD videa. Prva je ubacivanjem micro SD kartice do 128GB i druga konektovanjem na postojeći NVR i integracijom sa postojećim video nadzorom.
- 6803 Kamera: 1080P HD sa uglom gledanja od 160°
Konekcija: 802.11 b/g/n Wi-Fi @2.4GHz
Napajanje: 16~24V AC ili DC 12V
Zastita: IP65
Radna temperatura: -30°C ~ 50°C (-22°F ~ 122°F)
Dimenzije: 46.8 × 23.5 × 123.2mm

132,00

110,00

SP-UB01 Sterilizator



- Uređaj koristi UV LED da sterilise površine i da ubije bakterije.
- Može se koristiti da sterilise manje predmete poput mobilnog telefona, novčanika, olovki, ključeva, slušalica i drugih uređaja koji mogu da se spakuju u sterilizator. Progresivni displej sa audio notifikacijom kada se proces završi. Uređaj beže generacije O3, bezbedan i bez štetnosti po okolinu
- 6802 10,000 sati rada LED, 100,000 sterilizacija
Vreme trajanja sterilizacije: 10 min
Napajanje: Micro-USB, (DC 5V,1A)
Temperatura: 0 to 40
Dimenzije: 217.5mm*122.5mm*59.5mm (spoljašnjost)
180 mm *100 mm *25 mm (unutrašnjost)
Za unutrašnju upotrebu

42,00

35,00